

## PRODUCT DATA SHEET

# WDG-HPIIC Flue Gas Oxygen and Combustibles Analyzer

Close-coupled convective design for high-particulate applications

The WDG-HPIIC is a direct-mounted combustion analyzer providing a continuous measurement of oxygen and combustibles in flue gas applications with high levels of particulate. It leverages a unique chimney-effect/convective sampling technology which offers the advantages of high-particulate sampling (typically characteristic of an insitu probe) with the high temperature and corrosion resistance of an extractive analyzer. The WDG-HPIIC is ideal for combustion optimization on applications in cement and lime kilns, foundry and metals production furnaces, power and steam boilers (coal, wood waste and heavy oil-fired) and black liquor recovery boilers. The analyzers can be provided with a separate Series 2000 controller and are offered in a range of mounting styles.

### Reliable

The WDG-HPIIC leverages convective sampling and relies on diffusion of the sample, which reduces the velocity of gas to eliminate the problem of "sand blasting" the probe. In addition, the analyzer does not use an aspirator, minimizing particulate plugging up the inner sample plumbing.

### Accurate

This analyzer utilizes the proven technology of zirconium oxide (ZrO<sub>2</sub>) for a net oxygen measurement. In addition, the catalytic detector measures combustibles within 0-2000 parts per million (ppm) for combustion optimization.

### Serviceable

Maintenance can be performed on the WDG-HPIIC without removing it from the process.



## KEY BENEFITS

- Suitable for high-particulate processes
- Completely field serviceable
- Suitable for flue gases up to 1537°C (2800°F)
- Weatherproof, stainless steel enclosure
- Four (4) alarms for high/low conditions
- Available option for HART communications
- Available options for hazardous locations Class I, Div. 2 and Class I, Div. 1
- Designed for combustion optimization to maximize fuel efficiency

## APPLICATIONS

- Rotary kilns
- Power boilers
- Recovery boilers
- Multiple hearth furnaces

## KEY MARKETS

- Cement and lime
- Sludge incineration
- Pulp and paper

PERFORMANCE SPECIFICATIONS

Sensor Specifications

<b>Principle of operation</b>	Zirconium oxide (ZrO <sub>2</sub> ) for net oxygen (O <sub>2</sub> ) measurement
<b>Output range</b>	Oxygen: From 0-1% to 0-100%; Combustibles: From 0-2,000 ppm to 0-10,000 ppm or from 0-1% to 0-5%
<b>Accuracy</b>	Oxygen: ±0.75% of measured value or ±0.05% oxygen, whichever is greater; Combustibles: ±2% of full-scale output range
<b>Response</b>	Oxygen: 90% of a step change <30 seconds with 24" probe
<b>Drift</b>	< 0.1% of cell output per month; < 0.005% O <sub>2</sub> per month with 2% O <sub>2</sub> applied
<b>Max temp/Probe type</b>	704°C (1300°F)/316 SS; 1024°C (1875°F)/310 SS; 1537°C (2800°F)/Ceramic
<b>Probe lengths</b>	0.60m, 0.91m & 1.21m (24in, 36in & 48in.)
<b>Max sample dew point</b>	200°C (392°F)
<b>Sample pressure</b>	±10 in. water gauge
<b>Environment</b>	Ambient temperature: -20° to 71°C (-5 to 160°F), -20 to 60°C (-5 to 140°F) with Div. 2 option. Relative humidity: 10% to 90%, non-condensing
<b>Enclosure</b>	Lift-off NEMA 3R, weather-resistant, stainless steel. Optional hinged NEMA 4X (IP56), explosion-proof, purged, and floor mount versions available
<b>Power requirements</b>	115 VAC, ±10%, 47-63 Hz, 600 VA max. (650 VA w/floor mount option); 230 VAC, ±10%, 47-63 Hz, 1850 VA max. (1900 VA w/floor mount option)
<b>Calibration gas requirements</b>	Use calibration gases @ 10 psig, 1.5 scfh (0.70 kg/cm <sup>2</sup> , 0.7 L/min.); O <sub>2</sub> span gas: Air or from 1.0% to 100% O <sub>2</sub> , balance nitrogen (N <sub>2</sub> ) O <sub>2</sub> zero gas: 2% or from 0.1% to 10% O <sub>2</sub> , balance N <sub>2</sub> ; Comb. span gas: 60 to 80% (ppm ranges) or 40 to 60% (% ranges) of the selected comb. recorder output range in certified mixture of CO + H <sub>2</sub> , 3-4% O <sub>2</sub> , balance N <sub>2</sub>

Series 2000 Control Unit Specifications

<b>Display</b>	Four-line x 20-character vacuum fluorescent. Displays combinations of O <sub>2</sub> , % or ppm combustibles, time & date, cell temp., user-programmable text, thermocouple mV or cell mV. Password protection, programmable pressure compensation and context-sensitive help are also provided
<b>Analog output</b>	Two isolated linear current outputs for oxygen and one for combustibles. Select O <sub>2</sub> , combustibles, cell temperature, thermocouple mV or cell mV. Each output can be 4-20 mA, 0-20 mA, 20-4 mA or 20-0 mA and is fully scalable. Hold or track during calibration and select degree of damping. Maximum load 1200 ohms
<b>Alarms</b>	Two independent O <sub>2</sub> alarms, each high or low selectable. One alarm can be assigned as O <sub>2</sub> , calibrate or verify. Set relays to energize or de-energize on alarm
<b>Contact rating</b>	0.5A, 30V, 10VA max. noninductive load, AC or DC
<b>Diagnostics</b>	Watchdog timer and service alarms. System test for A/D, RAM, EEPROM, and keypad. Display line 4 reserved for full text error and diagnostic messages. 20-entry event log
<b>Communications</b>	RS485, 2-way addressable
<b>Environment</b>	Ambient temperature: -10 to 50°C (14 to 122°F); Relative humidity: 10 to 80%, non-condensing
<b>Enclosure</b>	Standard weatherproof NEMA 4 (IP 56) wall/panel mount. Optional GP (General Purpose) wall mount, GP 19in rack mount, GP panel mount, or stainless steel weatherproof NEMA 4X (IP 56) wall/panel mount. All are UL Listed for NEC Class I, Division 2 areas. Purged and explosion-proof versions also available
<b>Calibration</b>	O <sub>2</sub> cell lifetime extender. Calibrate or verify calibration. Store last calibration and verification data. Selectable calibration gas run time and process recovery time. Timed automatic calibration with optional Remote Calibration Unit
<b>Power requirements</b>	Nominal 115 to 230 VAC ±10%, 47 to 63 Hz, 75 VA max
<b>System compliance</b>	EMC Directive: 2004/108/EC; Low Voltage Directive: 73/23/EEC

New England - ETA Process Instrumentation  
119 Foster Street, Bldg #6  
Peabody, MA 01960  
Tel: (978) 532-1330  
www.etapii.com  
sales@etapii.com

Upstate NY - Martech Controls  
2000 Teall Avenue  
Syracuse, NY 13026  
Tel: (315) 876-9120  
www.martechcontrols.com  
sales@martechcontrols.com



© 2019, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0203 Rev 9 (0219)  
One of a family of innovative process analyzer solutions from AMETEK Process Instruments.  
Specifications subject to change without notice.

